

U.S. Serial No. 09/784,885

Resubmitted Response to Office Action Dated: 05/19/2004  
Family Number: P1998J135A

Page 2 of 9

AMENDMENT TO THE SPECIFICATION

Page 10, delete the following:

A preferred fuel has the following properties:

$T_{10}$ , °F  $\leq$  140;  $T_{50}$ , °F  $> 215 \leq 220$ ;  $T_{90}$ , °F  $< 330$  RVP, psi  $\leq 7.0$ ; S, ppmw  $\leq 50$ ; oxygen, wt%  $\leq 3.5$ ; aromatics, vol% of not more than 28; olefins, vol%  $\leq 10$ ; benzene, vol%  $< 1.0$ ; paraffins, vol%  $\leq 75$ ; API°  $\geq 59$ .

Another preferred fuel has the following properties:

$T_{10}$ , °F  $\leq$  140;  $T_{50}$ , °F  $> 215 \leq 220$ ;  $T_{90}$ , °F  $< 330$  RVP, psi  $\leq 7.0$ ; S, ppmw  $\leq 50$ ; oxygen, wt%  $\leq 1.5-2.9$ ; aromatics, vol%  $\leq 35$ ; olefins, vol%  $\leq 10$ ; benzene, vol%  $< 1.0$ ; paraffins, vol%  $\leq 75$ ; API°  $\geq 59$ .

Preferably, the fuels have a RVP psi of 6.6 to 6.9, more preferably a RVP psi of 6.6 maximum, a  $T_{90}$  °F of 315-330, more preferably 315-325, a  $T_{50}$  °F of 215 to 218, a sulfur content in ppmw of  $\leq 35$ , preferably not more than 25, an oxygen content in wt% of  $\leq 2$ , an aromatics content of not more than 28 vol%, more preferably 10 to 20 vol%, and a benzene content of not more than 0.80 vol%, preferably not more than 0.70 vol%.